



A DIVISION OF CRETE HOLDINGS P/L
ABN 28 282 241 891 ACN 003 822 526

DUROBOND PAINTS

65 OLD PITTWATER ROAD
BROOKVALE NSW 2100
Telephone: +61 2 9905 0811
Facsimile: +61 2 9905 6249
Email: durobond@durobond.com.au
Web: www.durobond.com.au

VERMICULITE RE-COAT (Water Based)

CODE: 362-06

Durobond Vermiculite Recoat is a dense, high opacity coating designed specially for application directly onto shabby Vermiculite ("popcorn") ceilings. The product bonds back any loose Vermiculite which when dry allows the new surface to be dusted and cleaned.

The resulting transformation from a dull and light absorbing ceiling to a brighter clean reflective surface is made possible by the hi-build formulation and the in-built resistance of the film to stain bleeding.

ADVANTAGES

Tropical Anti-Mould Formula
High opacity covers most stains
Formulation bonds, seals and blocks
Low V.O.C's
Non-toxic water based coating
Topcoat with water or enamel based finishes

Application Specification:

Read all information carefully before commencing application.

If you're not sure about any stage of application call Durobond for advice.

Repairing Vermiculite:

Before rejuvenating vermiculite ceilings, it will often be necessary to repair sections that have been damaged or have fretted. Using vermiculite with a specially developed Durobond Binder, gaps and gouges in the ceiling can be blended in making them difficult to detect after the application of Durobond Vermiculite Recoat.

Surface Preparation:

After doing any repair work that may be necessary, the whole surface area needs to be free from dust and cobwebs. Clean/ dust gently with soft broom or duster being careful not to dislodge any Vermiculite.

Surface temperature to be above 12°C and below 30°C at time of painting application.

Application:

Airless spray or long nap roller (20mm)
If spraying use a 17 thou tip or larger

Stirring:

Stir well with a broad flat paddle before and during use. Do not shake the can as this may aerate the paint and cause air bubbles in the coating.

Spread Rate:

Due to Vermiculite / Popcorn ceilings being very absorbent the spread rate varies enormously depending on how the product is applied (sprayed or rolled) and the finished look required.

If required up to 10% water maybe added which will help to extend the spread rate.

We suggest each coat not be "overloaded" with paint. This will provide a more even film and better sealing back of stains.

Four (4) coats usually provides a great bright new look to old dull ceilings but at times an extra coat maybe required.

The more coats you apply the better the end result.

You may top coated with Durobond Ceiling Matt White if required.

Method:

During application avoid heavy overlapping of product. This will prevent tram line effect. Allow the full dry time period as stated below. This will allow for better blocking of the next coat.

Remember – the more coats you apply the better the end result.



A DIVISION OF CRETE HOLDINGS P/L
ABN 28 282 241 891 ACN 003 822 526

DUROBOND PAINTS

65 OLD PITTWATER ROAD
BROOKVALE NSW 2100
Telephone: +61 2 9905 0811
Facsimile: +61 2 9905 6249
Email: durobond@durobond.com.au
Web: www.durobond.com.au

Dry Time:

Between coats allow to dry then allow minimum 4 hours after the Vermiculite Recoat is dry to touch before applying a 2nd and subsequent coats. If required topcoat with Durobond Ceiling Matt White after Vermiculite Recoat has dried.

Clean Up:

Clean up with water before equipment dries.

Shelf Life:

Unopened - 18 months from date of manufacture - after this time check with Durobond before use.

Storage:

Store in a cool, safe area away from children. Protect from direct sunlight and frost.

Health and Safety:

Wear protective clothing and eye protection as recommended by Workcover Australia.

A little "Vaseline™" on any exposed area of skin before commencing spray painting with Vermiculite Recoat will make for easy removal of the product should you get any splash back.

Keep doors and windows open to provide adequate ventilation during use and while drying.

For Safety and First Aid instructions refer to the Durobond Label or the Material Safety Data Sheet for any further information.

Transport:

Not classified as Dangerous Goods

Protect The Environment

Never dispose of unwanted paint down sewers or drains. Unwanted paints should be set aside in sealed, labelled containers and stored in a safe area for special waste collections. Refer to your local authority for the correct disposal advice.

DISCLAIMER

The uses of this product being beyond the control of the manufacturers, it is the responsibility of the user to satisfy him/herself that the preparation, product and application suits the job. Durobond Paints can accept no responsibility whatsoever for any loss or damage arising from incorrect use. Contractors applying Durobond Products are not employed by Durobond Paints. They are responsible for any warranties associated with their work, and the client must be satisfied with the conditions entered into with the contractor. The use of other manufacturer's products under or over Durobond's product(s) voids all warranties. Refer to Durobond Paints for any further enquiries you may have before proceeding with application.

Continuing research in the Durobond Laboratory leads to regular product updating. Check that you have the latest technical information.
This information supersedes all previous data information.